

19074 PAN File Report: Canadian Solar CS6K-275M Module

Report Number: 19074-PR-E-005
Report Date: 2019-12-20
Test Period: 2019-11-04 to 2019-12-05
Project ID: 19074 (CFV), 2109144 (Customer PO)
Customer: Joshua Stein / Sandia National Laboratories / PO Box 5800 MS1484 / Albuquerque, NM 87185-1484

Report Prepared by: Colin Sillerud – Project Engineer	Report Reviewed by: Jim Crimmins – General Manager
--	---

1 Project Summary

CFV Solar conducted PAN file testing on one **CS6K-275M** module produced by **Canadian Solar**. I-V curves at multiple irradiance and temperature conditions were obtained on one sample per IEC 61853-1:2011. The PVsyst 6 single-diode model coefficients were derived with PANOpt®, a software developed at CFV.

2 Executive Summary of Results

The performance matrix data were scaled to prepare PAN file source data for the 275 W power class of the CS6K-275M type. The “Measured STC” scaling method (explained in Procedures section) was used. Optimized PAN files were created for the specified module type and power class with PANOpt®, CFV’s proprietary software.

Table of Contents

1	Project Summary.....	1
2	Executive Summary of Results	1
	Disclaimer and Conditions of Report Reproduction.....	2
3	Sample Information	3
4	Procedures	5
4.1	Electroluminescence Imaging.....	5
4.2	Preconditioning	5
4.3	MQT 06.1 Performance at STC.....	5
4.4	Performance Matrix	6
4.5	MQT 04 Temperature Coefficients	8
4.6	Performance Data Scaling.....	8
4.7	PAN file Generation and Optimization.....	8
5	Results.....	9
5.1	Electroluminescence Imaging.....	9
5.2	Preconditioning	9
5.3	MQT 06.1 Performance at STC.....	10
5.4	MQT 04 Temperature Coefficients.....	10
5.5	Performance Matrix	12
5.6	Performance Matrix Data Scaling	13
5.7	PAN file Generation and Optimization.....	14

Disclaimer and Conditions of Report Reproduction

The results in this report relate only to the items tested.

This report contains no opinions, interpretations, or failure analysis.

This report may not be reproduced except in full, without the written consent of the testing laboratory.

3 Sample Information

Other samples were also tested as part of project 19074. For full information on all samples, refer to reports 19074-PR-E-001 through 19074-PR-E-009.

Labeling

Module ID	SNL ID	Manufacturer	Module Type	Serial Number
19074-005	00003259	Canadian Solar	CS6K-275M	11612480560332

Constructional Details

Module Type	Length [m]	Width [m]	Thickness [mm]
CS6K-275M	1.650	0.992	40

Nameplate Values

Module Type	Isc [A]	Voc [V]	Imp [A]	Vmp [V]	Pmp [W]	Max Sys Volt [V]	Fuse Rating [A]
CS6K-275M	9.31	38.3	8.80	31.3	275	1000	15

Photographs

Front



Back



Connectors



Junction Box



Nameplate(s)



Sampling

A single fielded sample of the type, CS6K-275M, was tested for this project and used in the PAN file creation.

4 Procedures

There were other tests included in project 19074. This report includes only the procedures relevant to the PAN file generation and Electroluminescence Imaging.

4.1 Electroluminescence Imaging

Electroluminescence (EL) images were taken with a Peltier-cooled CCD camera that has a resolution of 8.3 MPixels. A long pass filter blocked incoming light with wavelength below 850 nm. A constant DC bias was applied to the modules while the imaging was performed in the dark.

A relevant IEC document (IEC TS 60904-13:2018) has been published recently. The EL imaging was carried out at $1.0 \times I_{sc}$ per a procedure in this document, but this test is not yet included in CFV's scope of ISO 17025 accreditation.

4.2 Preconditioning

The sample was installed outdoors on a fixed rack in open circuit to receive a minimum of 40 kWh/m² of irradiation. The plane-of-array irradiance was measured with a calibrated pyranometer. CFV is ISO 17025-accredited to carry out Preconditioning per IEC 61215:2005. The preconditioning carried out for this project deviated from IEC 61215:2005 in that a higher irradiation dose was received (IEC 61215:2005 specifies a dose of 5.0 to 5.5 kWh/m²).

4.3 MQT 06.1 Performance at STC

Performance at STC test was carried out in conformity with IEC 61215-2:2016 MQT 06.1. CFV is ISO 17025-accredited to carry out the test. This test also qualifies as MQT 02 Maximum Power Determination.

We used a pulse-type solar simulator (Halm moduleTest 3; Fig. 4.3.1), classified as class AAA per IEC 60904-9:2007. The irradiance of the Xenon arc lamp flash at the module plane was measured with a co-planar reference cell (Fraunhofer WPVS type, manufactured by Czibula & Grundmann GmbH) that meets the requirements of IEC 60904-2:2015. The reference cell was calibrated at PTB of Germany. The solar simulator was in a room constantly maintained at $25 \pm 1^\circ\text{C}$, and prior to the tests we waited for the modules to thermally stabilize to the room temperature. During the test, the module backside temperature was measured at four points with calibrated RTDs with accuracy better than $\pm 0.2^\circ\text{C}$.

The reported I-V characteristics show the average of three consecutive measurements. Each measurement was carried out in conformity with IEC 60904-1:2006. One measurement involved a forward sweep (I_{sc} to V_{oc}) and a reverse sweep (V_{oc} to I_{sc}), whose I-V data were averaged to calculate the I_{sc} , V_{oc} , I_{mp} , and V_{mp} values. The irradiance was controlled to be within $1000 \pm 3 \text{ W/m}^2$ for the measurements. The minimal differences between the STC and the actual test conditions were further corrected per IEC 60891:2009.

Prior to measurements, testing was carried out to check for I-V curve hysteresis between the forward and reverse sweeps. It was found that the CS6K-275M module type needed only one section for both the forward and reverse sweeps. The effective sweep time for the measurements on the CS6K-275M module type was 25 ms forward and 25 ms reverse. A spectral mismatch factor of 1.0 was used as no EQE data was available for this module type.



Fig. 4.3.1 Class AAA solar simulator from h.a.l.m. used at CFV

Table 4.3.1 shows the uncertainty and repeatability of CFV's STC performance data. The values take in to account all the major sources of error, including the reference cell calibration, spectrum of the flasher, non-uniformity of the irradiance in the test plane, etc. CFV maintains a rigorous daily, weekly, and quarterly quality control program to guarantee top-tier flash measurement accuracy. The quarterly control modules are also measured annually at Fraunhofer ISE CalLab of Germany.

4.4 Performance Matrix

Multi-irradiance and multi-temperature Performance Matrix test was conducted in conformity with IEC 61853-1:2011 § 8.1. CFV is ISO 17025-accredited to carry out this test.

The test points cover irradiances from 100 to 1100 W/m², and temperatures from 15 to 75°C. In addition to the test points defined in IEC 61853-1:2011 § 8.1, measurements were obtained at five additional points, as shown in Table 4.4.1. The irradiance was varied by adjusting the voltage applied to the Xenon arc lamp. The spectral match remains class A or better for all irradiances. An integrated thermal chamber varied the module temperature

with a laminar air flow, and the module temperature was monitored at 4 points with calibrated RTDs having uncertainties of $\pm 0.13^{\circ}\text{C}$. For each measurement, the max-min temperature spread was less than 1.5°C .

The monitor cell was mounted at a location outside the thermal chamber and was not coplanar with the test module. The monitor cell sensitivity was adjusted to reproduce the Pmp measured at STC on the test module. Other than the irradiance and temperature controls, the measurement procedure was identical to the Performance at STC test.

Table 4.4.1: Test points for the performance matrix. 5 additional test points are indicated.

Irradiance (W/m ²)	Temperature			
	15°C	25°C	50°C	75°C
1100		⊙	⊙	⊙
1000	⊙	⊙	⊙	⊙
800	⊙	⊙	⊙	⊙
600	⊙	⊙	⊙	⊙
400	⊙	⊙	⊙	⊗
200	⊙	⊙	⊗	⊗
100	⊙	⊙	⊗	⊗

⊙ Measured and required by the IEC 61853-1 standard

⊗ Additional test points; Measured but not required by the IEC 61853-1 standard

4.5 MQT 04 Temperature Coefficients

Temperature Coefficients test was conducted in conformity with IEC 61215-2:2016 MQT 04 and IEC 60891:2009 § 4. CFV Solar is ISO 17025-accredited to carry out the test.

The test was carried out along with the Performance Matrix test. In addition to the 15, 25, 50, and 75°C temperatures required for the matrix, the modules were flashed with 1000 W/m² irradiance at additional intermediate temperatures. The temperature coefficients for I_{sc}, V_{oc}, I_{mp}, V_{mp}, and P_{mp} were determined by linear regression over the 15-75°C temperature range.

4.6 Performance Data Scaling

When creating PAN files for PVsyst, one requirement is that the P_{mp} at STC needs to match the nameplate power. This requirement translates into the technical issues of (1) how to scale the P_{mp} values at the various temperature and irradiance points and (2) how to scale the STC I_{sc}, V_{oc}, I_{mp}, and V_{mp} values, if the measured values at STC do not match the nameplate values.

In this project, we scaled the performance matrix data for use with PANOpt®, by the following approach:

Measured STC Approach

Pmp	A constant gain factor was applied to the Pmp values in the matrix, to obtain the nameplate rating at STC. The gain factor used was: $[Pmp\ Gain] = [NP\ Pmp] / [Measured\ STC\ Pmp]$
Isc, Voc, Imp, Vmp	A constant gain factor equal to the square root of [Pmp Gain] was applied to the I _{sc} , V _{oc} , I _{mp} , and V _{mp} values. $[Isc\ Gain] = [Voc\ Gain] = [Imp\ Gain] = [Vmp\ Gain] = [Pmp\ Gain]^{1/2}$

4.7 PAN file Generation and Optimization


Optimized PAN files were prepared using PANOpt®, an in-house-developed software for deriving from the test data optimum solutions for the PVsyst 6 single-diode performance model. Starting with the measured values of I_{sc}, V_{oc}, I_{mp}, V_{mp}, mul_{sc}, and an R_s value calculated from the I-V curves with the Swanson method, the PANOpt® solver iterated over a given parameter space for R_s, R_{sh}, R_{shG0} (and di²/μτ_{eff} for thin-film technologies) until the PVsyst 6 model-predicted P_{mp} values over the Performance Matrix points matched the measured values (average of three samples) with minimum error.

The IAM profile of the test module was not experimentally determined. The default PVsyst IAM profile for normal glass was adopted.

5 Results

5.1 Electroluminescence Imaging

The module was imaged in the dark while a constant DC bias current of 9.31 A (I_{sc}) was applied to the module.



5.2 Preconditioning

The module received 41.33 kWh/m² of outdoor preconditioning prior to indoor performance testing. The preconditioning was performed with the module in open circuit.

5.3 MQT 06.1 Performance at STC

The following values were measured during the Performance Matrix test following preconditioning.

Module ID	Isc [A]	Voc [V]	Imp [V]	Vmp [V]	Pmp [W]	FF [%]
19074-005	9.299	38.29	8.810	31.48	277.37	77.89

Table 5.3.1 Uncertainty and repeatability of flash measurements on Si modules

	Isc	Voc	Imp	Vmp	Pmp
Uncertainty	± 1.8 %	± 0.7 %	± 2.2 %	± 1.3 %	± 2.2 %
Repeatability	± 0.20 %	± 0.20 %	± 0.30 %	± 0.40 %	± 0.45 %

5.4 MQT 04 Temperature Coefficients

Relative Units

Module ID	α Isc [%/°C]	β Voc [%/°C]	α Imp [%/°C]	β Vmp [%/°C]	δ Pmp [%/°C]
19074-005	+0.0355	-0.3078	-0.0160	-0.4023	-0.4155


Absolute Units


Module ID	α Isc [A/°C]	β Voc [V/°C]	α Imp [A/°C]	β Vmp [V/°C]	δ Pmp [W/°C]
19074-005	+0.00330	-0.1178	-0.00141	-0.1266	-1.1522

Table 5.4.1 Estimated uncertainty of temperature coefficients (relative)

	α Isc	β Voc	α Imp	β Vmp	γ Pmp
Uncertainty (k = 2)	± 10 %	± 5 %	N/A	N/A	± 5 %

Plots





Measured Data


The following table shows the I-V values measured on the tested sample.

Module ID	T (°C)	G (W/m ²)	Isc (A)	Voc (V)	Imp (A)	Vmp (V)	Pmp (W)
19074-005	15.34	1000	9.263	39.42	8.814	32.71	288.28
19074-005	20.13	1000	9.276	38.85	8.814	32.09	282.87
19074-005	24.92	1000	9.299	38.30	8.810	31.49	277.44
19074-005	29.83	1000	9.327	37.70	8.816	30.82	271.71
19074-005	34.68	1000	9.348	37.14	8.810	30.21	266.12
19074-005	39.85	1000	9.361	36.53	8.801	29.58	260.28
19074-005	44.69	1000	9.381	35.96	8.801	28.94	254.70
19074-005	49.85	1000	9.385	35.37	8.784	28.31	248.65
19074-005	54.75	1000	9.405	34.78	8.780	27.68	243.00
19074-005	59.69	1000	9.424	34.19	8.770	27.06	237.32
19074-005	64.70	1000	9.432	33.61	8.757	26.44	231.55
19074-005	69.61	1000	9.443	33.02	8.743	25.83	225.81
19074-005	75.02	1000	9.455	32.39	8.724	25.18	219.65

5.5 Performance Matrix

Efficiency Curves

In the following plot, circles indicate the average of three measurements at each irradiance and temperature test condition. Bars inside the circles indicate the values from each of the three measurements.



Measured Data

The following table shows the Performance Matrix data measured on the tested sample.

Module ID	T (°C)	G (W/m2)	Isc (A)	Voc (V)	Imp (A)	Vmp (V)	Pmp (W)
19074-005	15	100	0.913	35.70	0.870	30.77	26.78
19074-005	15	200	1.830	36.81	1.750	31.63	55.34
19074-005	15	400	3.664	37.94	3.506	32.38	113.50
19074-005	15	600	5.533	38.61	5.284	32.65	172.54
19074-005	15	800	7.387	39.08	7.041	32.74	230.50
19074-005	15	1000	9.262	39.46	8.813	32.74	288.54
19074-005	25	100	0.922	34.40	0.871	29.41	25.61
19074-005	25	200	1.833	35.56	1.752	30.31	53.11
19074-005	25	400	3.677	36.73	3.506	31.07	108.93
19074-005	25	600	5.550	37.43	5.274	31.36	165.40
19074-005	25	800	7.420	37.92	7.034	31.47	221.38
19074-005	25	1000	9.299	38.29	8.810	31.48	277.37
19074-005	25	1100	10.229	38.47	9.685	31.46	304.73
19074-005	50	100	0.934	31.14	0.869	26.09	22.68

Module ID	T (°C)	G (W/m ²)	Isc (A)	Voc (V)	Imp (A)	Vmp (V)	Pmp (W)
19074-005	50	200	1.862	32.39	1.751	27.04	47.36
19074-005	50	400	3.723	33.66	3.502	27.82	97.44
19074-005	50	600	5.610	34.41	5.271	28.14	148.34
19074-005	50	800	7.490	34.95	7.027	28.27	198.65
19074-005	50	1000	9.385	35.35	8.785	28.29	248.55
19074-005	50	1100	10.322	35.54	9.650	28.30	273.06
19074-005	75	100	0.941	27.79	0.869	22.71	19.73
19074-005	75	200	1.877	29.16	1.744	23.73	41.39
19074-005	75	400	3.753	30.54	3.490	24.60	85.87
19074-005	75	600	5.649	31.36	5.233	24.97	130.66
19074-005	75	800	7.548	31.94	6.986	25.12	175.45
19074-005	75	1000	9.455	32.39	8.724	25.18	219.67
19074-005	75	1100	10.414	32.58	9.595	25.17	241.55

5.6 Performance Matrix Data Scaling

The gain factors were calculated as explained in the procedures section.

Measured STC values of the single test module

Measured Power Class	Measured STC Isc (A)	Measured STC Voc (V)	Measured STC Imp (A)	Measured STC Vmp (V)	Measured STC Pmp (W)
275	9.299	38.29	8.810	31.48	277.37

Applied gain factors for PAN file STC values by power class

PAN File Power Class	Isc Gain	Voc Gain	Imp Gain	Vmp Gain	Pmp Gain
275	0.9957	0.9957	0.9957	0.9957	0.9914

PAN file STC values by power class

PAN File Power Class	PAN File STC Isc (A)	PAN File STC Voc (V)	PAN File STC Imp (A)	PAN File STC Vmp (V)
275	9.259	38.13	8.773	31.35

5.7 PAN file Generation and Optimization

PAN File Parameters for 275 W Class

Tab	Parameter	275 W
Basic data	Model	CS6K-275M
	Manufacturer	Canadian Solar
	File name	Canadian Solar_CS6K-275M_Dec2019_CFV.PAN
	Data source	CFV Solar Test Lab - Tested Class
	Nom. Power (Wp)	275
	Tol. - (%)	0
	Tol. + (%)	5
	Technology	Si-mono
	GRef (W/m2)	1000
	TRef (°C)	25
	Isc (A)	9.259
	Voc (V)	38.13
	Imp (A)	8.773
	Vmpp (V)	31.35
mulsc (%/°C)	0.035	
Sizes and Technology	Length (mm)	1650
	Width (mm)	992
	Thickness (mm)	40
	Cells in series	60
	Maximum voltage IEC (V)	1000
	Maximum voltage UL (V)	1000
	Nb. of sub-modules	3
	Sub-module partition	Full Cells
Model parameters / Rshunt - Rserie	Rsh (Ohm)	604
	Rs (Ohm)	0.215
Model parameters / RShunt expon.	Rshunt at Ginc = 0 (Ohm)	1870
	Exponential parameter	5.5
Model parameters / Temper. coeff	Apply Temperature Correction on Gamma	Checked
	Pmpp temper. Coeff ¹	-0.412
Additional data /	Special IAM defined for this module	Unchecked

¹ The Pmp temperature coefficient in PVsyst is different from the definition in IEC 60891:2009. In PVsyst, the Pmp temperature coefficient is calculated from the Pmp values at 25°C and 45°C. Per IEC 60891:2009, the Pmp temperature coefficient is to be calculated by a linear fit through Pmp values measured over a temperature range greater than or equal to 30°C. There is in fact some nonlinearity in the Pmp dependence on temperature, which is why the Pmp temperature coefficient value for the PAN file is different from the value reported in Section 04.


Tab	Parameter		275 W
Customized IAM	Front Surface		Normal Glass
	Point 1	0°	1.000
	Point 2	30°	0.998
	Point 3	50°	0.981
	Point 4	60°	0.948
	Point 5	70°	0.862
	Point 6	75°	0.776
	Point 7	80°	0.636
	Point 8	85°	0.403
	Point 9	90°	0.000

PAN File Model Accuracy

PVsyst 6 model output was compared with the scaled data used as the PANOpt® input.

Power Class	RMS Error of Pmp (Error = PVsyst 6 model Pmp - Measured Pmp) [W]				
	15-75°C	15°C	25°C	50°C	75°C
275 W	0.22	0.22	0.23	0.25	0.18

Module Type	RMS Error of Eff. (Error = PVsyst 6 model Eff. - Measured Eff.) [%p]				
	15-75°C	15°C	25°C	50°C	75°C
275 W	0.029	0.034	0.035	0.016	0.016



--END OF REPORT--